AC Surge Protector SPD I2R-T240 DIN-Rail 120 Vac 3-Phase Wye MOV 40 kA, IEC 61643-11 Class II, CE, RoHS

I2R-T240-4P120



Features

- IEC61643-11 Class II
- High Capacity MOV Protection
- Visual Suppression Status Indicator
- Dry Contact Remote Annunciation Wire Leads
- Replaceable Suppression Modules
- Wire and Comb Busbar Wiring Terminals
- Reversible Chassis for Top or Bottom Wiring
- DIN-Rail Mount
- Dry Contact Remote Annunciation Terminals

Applications

- Electrical Panelboards
- Industrial Automation
- Communications Base Stations
- IT & Data Centers
- Switchgear
- Motor Control Centers
- Automatic Transfer Switches
- Wastewater Treatment
- Oil & Gas
- LED Lighting
- Schools
- Hospitals
- Mining
- Photovoltaic and Wind

Description

AC surge protector (also known as SPD or lightning protector) I2R-T240-4P120 from Transtector is a DIN-Rail style SPD that utilizes state of the art MOV technology to protect critical equipment that operates on a 120 Vac 3-Phase Wye electrical service. This surge protector provides effective protection against electrical transient surges that are generated both by external lightning events and by internal switching events and supports long-term system reliability by safely shunting high amounts of transient energy while maintaining a very low clamping voltage. Transtector AC surge protectors are available in stock with same day shipping.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Service Voltages		120		Vac
Service Type		3-Phase Wye		
Maximum Continuous Operating Voltage (MCOV)				
L - N			150	Vac
Backup Fuse		125		A gL/gG

Surge Protection Specification

Description	Minimum	Typical	Maximum	Units
Surge Protection Technology		MOV		

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications:
AC Surge Protector SPD I2R-T240 DIN-Rail 120 Vac 3-Phase Wye MOV 40 kA, IEC 61643-11 Class II, CE, RoHS I2R-T240-4P120

I2R-T240-4P120 REV 1.1 | © 2019 Transtector, Inc., All Rights Reserved.

AC Surge Protector SPD I2R-T240 DIN-Rail 120 Vac 3-Phase Wye MOV 40 kA, IEC 61643-11 Class II, CE, RoHS

I2R-T240-4P120



Protection Modes	L-N, N-PE		
8/20µs Surge Current		40	kA
Nominal Discharge Current Rating (In)	20		kA
VPR 8/20µs			
L - N		1,000	Vpk
Response Time		25	ns
SCCR (Short Circuit Current Rating)	25		kAIC

Mechanical Specifications

Size

Height	2.992 in	[76 mm]
Width	3.543 in	[89.99 mm]
Depth	2.835 in	[72.01 mm]
Weight	0.92 lbs	[417.3 g]
Housing Material and Plating	PA66 CT1; V-0	

Environmental Specifications

Temperature Range (Operational)	-40 to +80 deg C
Temperature Range (Storage)	-40 to +80 deg C
Environmental Protection Rating	IP 20
Humidity	90% non-condensing

Installation

Mount Type	DIN Rail
Service Wiring Terminal	
Compression Lug	#1 to #9 AWG
Status Indication Terminal	
3-Position Screw Terminal	#16 to #22 AWG

Compliance Certifications

REACH Compliant	06/29/2018
RoHS Compliant	Yes
CE Compliant	Yes
Certifications	IEC 61643-11 Class II

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications:
AC Surge Protector SPD I2R-T240 DIN-Rail 120 Vac 3-Phase Wye MOV 40 kA, IEC 61643-11 Class II, CE, RoHS I2R-T240-4P120

I2R-T240-4P120 REV 1.1 | © 2019 Transtector, Inc., All Rights Reserved.

AC Surge Protector SPD I2R-T240 DIN-Rail 120 Vac 3-Phase Wye MOV 40 kA, IEC 61643-11 Class II, CE, RoHS



I2R-T240-4P120

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.


Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: AC Surge Protector SPD I2R-T240 DIN-Rail 120 Vac 3-Phase Wye MOV 40 kA, IEC 61643-11 Class II, CE, RoHS I2R-T240-4P120

URL: https://www.transtector.com/ac-surge-protector-spd-i2r-t240-din-i2r-t240-4p120-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

I2R-T240-4P120 CAD Drawing

REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	1/17/19	DWR



UNLESS OTHERWISE SPECIFIED
LEADING DIMENSIONS ARE INCHES
DIMENSIONS IN [ ] ARE MILLIMETERS
TOLERANCES:
X± .2 [5.08] | FRACTIONS ± 1/32
.XX± .01 [.25] | ANGLES ± 1°
.XXX± .005 [.13]
ALL DIMENSIONS SHOWN ARE FOR REFERENCE ONLY.
THIRD-ANGLE PROJECTION

THE INFORMATION AND DESIGN IN THIS DOCUMENT IS THE PROPERTY OF TRANSTECTOR CORPORATION. ALL RIGHTS RESERVED.

TRANSTECTOR
10701 AIRPORT ROAD, HAYDEN, ID. 83835
PHONE: 1.208.635.6400 | 1.800.882.9110
FAX: 1.208.955.2041
www.transtector.com | e-mail: sales@transtector.com

SIZE	CAGE	DRAWN BY	PART NUMBER	REV
A	30992	HMB	I2R-T240-4P120	A

SHEET 1 OF 1
SCALE NTS

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

T-Rev A

I2R-T240-4P120 REV 1.1 | © 2019 Transtector, Inc., All Rights Reserved.