TRANSTECTOR
an INFINITE brand

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT, Solid State Thermostat Heat & Fan Gray



TEF141207-1HFS

Features

- Molded Fiberglass Reinforced Polyester (FRP) industrial enclosure
- Stainless steel quick release latches with padlock hasps
- NEMA Type 3R / IP24 rated
- Fully gasketed raised vented lid with filters & integral mounting flange
- Features aluminum mounting plate with surge protected duplex 120 VAC outlets & solid state thermostat controlled heating & cooling system

Applications

- Remote wireless LAN WiFi equipment installations
- Indoor and outdoor installations
- Rapid deployment installations
- Corrosive environments & hotspot
- Protection of equipment from theft or damage

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded fiberglass reinforced polyester, it is well suited for high temperature or corrosive environments. The mounting flange allows it to be wall mounted as well as on a flat surface. The raised lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. Includes fully gasketed raised vented lid with filters & integral mounting flange. The enclosure material is UV stabilized and comes in machine tool gray.

120 VAC Mounting Plate with Lightning Protection

The aluminum mounting plate features standard surge protected duplex 120 VAC outlets and a terminal block for easy hook up to the externally provided line power. In addition, the unit can accept up to two optional bulkhead mount N-type lightning protectors to protect the coaxial cable runs.

To help ensure trouble-free operation of electronic equipment, proper operating temperatures inside an enclosure needs to be maintained. With the built-in heater and cooling fan, internal temperatures can be better maintained. This model is ideal in hot and/or cold environments.

The TEF141207-1HFS comes with a 120 VAC 200 watt heating element and 120 VAC cooling fan. The fan and heater are controlled by our exclusive solid state temperature controller. The standard unit has a fan turn-on temperature of 93° F (34° C) ±5° and a heat turn-on temperature of 16° F (-9° C) ±5°. The heater and fan are controlled by two integral high current solid state AC relays. The relays feature zero cross detection for EMI reduction. No extra room for the controller is required since it is mounted underneath the plate.

Size

Outer Height	15.5 in	[393.7 mm]
Outer Width	13.32 in	[338.33 mm]
Outer Depth	8.26 in	[209.8 mm]
Inner Height	14 in	[355.6 mm]
Inner Width	12 in	[304.8 mm]
Inner Depth	7.95 in	[201.93 mm]
Weight	13 lbs	[5.9 kg]

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT, Solid State Thermostat Heat & Fan Gray TEF141207-1HFS

TEF141207-1HFS REV 1.0 | © 2019 Transtector, Inc., All Rights Reserved.

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT, Solid State Thermostat Heat & Fan Gray



TEF141207-1HFS

Enclosure Material and Plating	Fiberglass Reinforced Polyester (FRP)

Environmental Specifications

Temperature Continuous	-50 to +150 deg C
NEMA Rating	3R
Ingress Protection (IP) Rating	IP24

Environmental Specification Notes:
Enclosure material is halogen-free, self-extinguishing FRP.

Compliance Certifications

UL Listed	No

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.


Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT, Solid State Thermostat Heat & Fan Gray TEF141207-1HFS

URL: https://www.transtector.com/14x12x07-fiberglass-reinf-polyester-frp-weatherproof-outdoor-tef141207-1hfs-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, 120 VAC MNT PLT, Solid State Thermostat Heat & Fan Gray

TEF141207-1HFS CAD Drawing



TEF141207-1HFS REV 1.0 | © 2019 Transtector, Inc., All Rights Reserved.