14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, PoE MNT PLT, Solid State Thermostat 48 VDC Fan Gray



TEF141207-40FS

Features

- Molded Fiberglass Reinforced Polyester (FRP) industrial enclosure
- Stainless steel quick release latches with padlock hasps
- NEMA Type 3R / IP24 rated
- Fully gasketed raised vented lid with filters with integral mounting flange
- Features aluminum mounting plate with Power-Over-Ethernet (PoE) interface with CAT5 surge protection & solid state controlled cooling system

Applications

- Remote wireless LAN WiFi equipment installations using Power-Over-Ethernet
- Indoor and outdoor installations
- Rapid deployment installations
- Corrosive environments
- Hotspot

Description

The box is a rugged weatherproof enclosure that is ideal for both indoor and outdoor applications. Constructed from molded fiberglass reinforced polyester, it is well suited for high temperature or corrosive environments. The mounting flange allows it to be wall mounted as well as on a flat surface. The raised lid features a stainless steel continuous hinge and stainless steel quick release latches with padlock hasps. Includes fully gasketed raised vented lid with filters & integral mounting flange. The enclosure material is UV stabilized and comes in machine tool gray.

The aluminum mounting plate included with the TEF141207-40FS, has provisions to mount WLAN equipment. The enclosure also features holes for two N-bulkhead lightning protectors or connectors, a grounding lug and cable conduit connector.

Power-Over-Ethernet (PoE)

The mounting plate features a CAT5 PoE interface that feeds power to the enclosure fan and power plus data to the internal network equipment. The enclosure is not 802.3af/at/bt PoE compatible. It requires one of our 48 volt DC PoE Midspan injectors to supply power. The interface includes lightning protection and support for normal and reverse polarity POE equipment. An optional 802.3af compatible PoE interface with surge protector can be added for a second CAT5 cable.

Solid State Fan Controller

The TEF141207-40FS comes with a high CFM 48 VDC cooling fan installed. The high airflow, low noise fan featuring sealed ball bearings, evacuates heat from the top of the enclosure. The fan is controlled by our exclusive solid state fan controller. The standard unit has a fan turn-on temperature of 90° F (32° C) and turns off at 81° F (27° C) with a hysteresis window of 9° F (5° C). No extra room for the controller is required since it is mounted underneath the plate.

Size

Outer Height	15.5 in	[393.7 mm]
Outer Width	13.32 in	[338.33 mm]
Outer Depth	8.26 in	[209.8 mm]
Inner Height	14 in	[355.6 mm]
Inner Width	12 in	[304.8 mm]
Inner Depth	7.95 in	[201.93 mm]

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications:
14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, PoE MNT PLT, Solid State Thermostat 48 VDC Fan Gray TEF141207-40FS

TEF141207-40FS REV 1.0 | © 2019 Transtector, Inc., All Rights Reserved.

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, PoE MNT PLT, Solid State Thermostat 48 VDC Fan Gray



TEF141207-40FS

Weight	12.28 lbs [5.57 kg]
Enclosure Material and Plating	Fiberglass Reinforced Polyester (FRP)

Environmental Specifications

Temperature Continuous	-50 to +150 deg C
NEMA Rating	3R
Ingress Protection (IP) Rating	IP24

Compliance Certifications

UL Listed	No

Transtector Systems specializes in protection of highly sensitive, low voltage equipment through its patented, non-degrading silicon diode technology and custom filters. Our power quality expertise translates into a diverse product offering including AC, DC, and signal applications as well as integrated cabinets, power distribution panels and EMP hardened devices.

Click the following link (or enter part number in “SEARCH” on website) to obtain additional part information including price, inventory and certifications: 14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, PoE MNT PLT, Solid State Thermostat 48 VDC Fan Gray TEF141207-40FS


URL: https://www.transtector.com/14x12x07-fiberglass-reinf-polyester-frp-weatherproof-outdoor-tef141207-40fs-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Transtector reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Transtector does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Transtector does not assume any liability arising out of the use of any part or documentation.

TEF141207-40FS REV 1.0 | © 2019 Transtector, Inc., All Rights Reserved.

14x12x07 Fiberglass Reinf Polyester FRP Weatherproof Outdoor IP24 NEMA 3R Enclosure, PoE MNT PLT, Solid State Thermostat 48 VDC Fan Gray

TEF141207-40FS CAD Drawing



TEF141207-40FS REV 1.0 | © 2019 Transtector, Inc., All Rights Reserved.